
CLAMP METER

- 2605B Digital DCA/ACA Clamp Meter



- 4000 counts digital display
- Auto ranging
- Auto power off
- Overload protections
- Safety input jacks
- Safety test leads
- Safety: EN61010-1, EN 61010-2-032, CAT IV 600V, CAT III 1000V, CE approved
- ♣ Jaw opening capability: 57mm conductor.
- Dimensions:281mm(H)×108mm(W)×53mm(D)
- Weight: Approx. 570g

SPECIFICATIONS

■ DC Current: 400A, 1000A ±2.0%

■ AC Current: 400A, 1000A ±2.0% (50-400Hz)

■ DC Volts: 400mV, 4V, 40V, 400V, 1000V ±0.5%

AC Volts: 400mV, 4V, 40V, 400V, 750V ±1.5% (50-500Hz)

Resistance: 400Ω, $4k\Omega$, $40k\Omega$, $400k\Omega$, $4M\Omega$, $40M\Omega \pm 1.0\%$

Frequency: 10Hz - 1MHz ±0.1%

Diode Test

■ Continuity Test

■ DATA Hold

■ DCA ZERO

📲 Resolution: 0.1A, 0.1mV, 0.1Ω, 1Hz

CHUNG INSTRUMENT ELECTRONICS INDUSTRIAL CO., LTD.