


DP-30K Differential Probe

SPECIFICATIONS:

FUNCTION / MODEL	DP-30K
Differential Voltage DC + AC peak	30KV
Bandwidth (50Ω load -3dB)	50MHz(25MHz at x200)
Common Mode Voltage DC + AC peak	30KV
Common Mode Voltage RMS CAT II / CAT III	11KVrms
Attenuation (Switchable)	X200, X2000
Input R (Each Input)	20MΩ ± 2%
Input C (Each Input)	2.6PF ± 5%
Maximum Operation Voltage (DC+ AC peak)	≤ 3.0KV at x 200 ≤ 30KV at x 2000
Common Mode Rejection Ratio (CMRR)	60 Hz: > 10000 : 1 100 Hz: > 1000 : 1 1MHz: > 300 : 1
Noise (Into 50Ω Load)	≤ 1.0m Vrms
Input Impedance (Between Input)	40MΩ // 1.3 PF
Accuracy (at 20~30°C 70%RH after 20 minutes)	≤ ± 2%
Maximum Output Voltage	≤ ± 8V
Power Source	External 9V DC Adaptor
Other	Over Range Indicate



ACCESSORIES:



PINTEK

Pintek Electronics Co., Ltd

2F No.32 Tai-Pen Rd., Shulin Dist., New Taipei City, Taiwan

Tel: 886-2-86859562~3 ; 886-2-86861898

Fax: 886-2-86852081 ; 886-2-86861114

<http://www.pintek.com.tw>

E-Mail : pintek@pintek.com.tw ; pintek@ms26.hinet.net

SALES AGENT