

Multi-functions

ELEVATOR TACHOMETER with Stroboscope

Model : DT-2337

ISO-9001, CE, IEC1010



Photo Tach

Contact Tach

Surface speed

Stroboscope

Type k thermometer

Pt 1000 ohm Temp.



Lutron

LUTRON ELECTRONIC

The Art of Measurement



TEST AND MEASUREMENT INSTRUMENTS C.C.
www.instrumentsgroup.co.za
Email: Sales@instrumentsgroup.co.za

Multi-functions

ELEVATOR TACHOMETER with Stroboscope

Model : DT-2337

FEATURES

- * Multi-functions, one instrument combine Photo Tachometer (RPM, rev/s) & Contact Tachometer (RPM, rev/s,m/min.,m/s,cm/s,km,m,km/h,ft/min.,in/min.),Stroboscope ,Type K Thermometer, Pt 1000 Thermometer.
- * High intensity white light beam for photo tachometer, safety and save the power energy.
- * Wide measuring range from 0.5 to 99,999 RPM.
- * 0.5 RPM resolution for the measured value < 1000 RPM.
- * High precision with 0.05% accuracy.
- * The last value, max., value, min. value will be stored into the memory automatically & can be obtained by pressing REC Button.
- * Large LCD display.
- * High visible LCD display gives RPM reading exactly with no guessing or errors & saves battery energy.
- * This tachometer used the exclusive one chip MICRO-COMPUTER LSI circuit & crystal time base, offer the high accurate measurement & fast sampling time.
- * The use of durable, long lasting components, including a strong, light weight ABS plastic housing, assures almost maintenance free performance for many years.
- * The housing cabinet has been carefully shaped to fit comfortable in either hand.

General Specifications

Display	43 mm x 33 mm LCD, 5 digits. 5 digits with display unit.
Measurement	1.Photo Tachometer : (RPM, rev/s) 2.Contact Tachometer : (RPM, rev/s,m/min.,m/s,cm/s, km,m,km/h,ft/min.,in/min.) 3. Stroboscope, 4. Type K Thermometer, 5. Pt 1000 Thermometer.
Operating Humidity	Max. 80% RH.
Operating Temperature	0 to 50 °C (32 to 122 °F)
Over Input Display	Indication of "----"
Power Supply	UM3-AA X 4 (DC 4.5 V battery)
Power Consumption	Approx. DC 52 mA
Weight	230g/0.50LB (Meter only)
Dimension	HWD 207 x 67 x 39 mm (81.5 x 26.3 x 15.3 inch).
Time base	Quartz crystal.
Circuit	Exclusive one-chip of microcomputer LSI circuit.
Memory	Last/Max./Min. value.
Accessories Included	Hard carrying case 1 PC. Reflecting tape marks (600 mm)..... 1 PC. RPM adapter (CONE)..... 1 PC. RPM adapter (FUNNEL)..... 1 PC. Surface speed test wheel..... 1 PC. Operation manual..... 1 PC. Surface speed test wheel Connecting rod.. 1 PC.
Optional	AC to DC adapter..... 1 PC. USB cable (USB-01)..... 1 PC. RS232 cable (UPCB-02)..... 1 PC. Data acquisition software (SW-U801-WIN) 1 PC. Excel data acquisition software(SW-E802). 1 PC. Type K Temp. probe : TP-01 , TP-02A ,TP-03 , TP-04 TP-05
Accessories	TP-1000 (Pt-1000 ohm Temp. probe.)

Electrical Specification (23 ±5 °C)

Photo Tachometer

Measurement & Range	<i>Photo Tachometer :</i> 5 to 99,999 RPM.
Resolution	RPM: 0.5 RPM (< 1,000 RPM). 1 RPM (≥ 1,000 RPM).
Accuracy	±(0.05% + 1 digit).
Photo Tachometer detecting distance	50 to 150 mm/2 to 6 inch. (typical max. 300 mm/12 inch, depending upon ambient light). * <i>Spec. of detecting distance are that under the size of reflecting tape is 10 mm square & the measuring RPM value is 1,800 RPM. The max. & min. detecting distance may change under different environment, different reflecting tape or the measuring RPM beyond 1800 RPM.</i>

Contact Tachometer

Measurement unit	Measurement Range	Resolution	Accuracy
RPM	0.5 ~ 999.5 1000 ~ 19999	1 1	±(0.05% + 1 digit)
rev/s	0.008 ~ 16.658 16.658 ~ 333.31	0.008 0.01	±(0.05% + 1 digit)
m/min.	0.05 ~ 99.95 100.0 ~1999.9	0.05 0	±(0.05% + 1 digit)
cm/s	0.08 ~ 166.58 166.6 ~ 3333.1	0.08 0.2	±(0.05% + 1 digit)
m/s	0.0008 ~ 1.6658 1.666 ~ 33.331	0.0008 0.001	±(0.05% + 1 digit)
km	0.0000 ~ 99999	0.0001 ~ 1	±(0.05% + 1 digit)
m	0.0008 ~ 99999	0.0001 ~ 1	±(0.05% + 1 digit)
km/h	0.003 ~ 5.997 6 ~ 119.99	0.003 0.01	±(0.05% + 1 digit)
ft/min.	0.1 ~ 327.8 328 ~ 6559	0 1	±(0.05% + 1 digit)
in/min.	1.9 ~ 3935.0 3937 ~78736	# 4	±(0.05% + 1 digit)

NOTE: When using test wheel, accuracy can be affected as much as 0.5% of reading.

Stroboscope Tachometer

Flash adjust range	100 to 99,990 RPM/FPM. * RPM : round per minute. * FPM : flash per minute.	
Resolution	0.1 RPM : < 1,000 RPM. 1 RPM : ≥ 1,000-30,000 RPM	5 RPM : ≥ 30,000-50,000 RPM 10 RPM : ≥ 50,000-99,990 RPM
Function buttons	Digital rotate knob, x 2 button, ÷ 2 button, + button, - button,	
Accuracy	±(0.1 % + 2d)	

Type K thermometer

Sensor Type	Resolution	Range	Accuracy
Type K	0.1 °C	-50.0 to 1300.0 °C -50.1 to -100.0 °C	± (0.4 % + 0.5 °C) ± (0.4 % + 1 °C)
	0.1 °F	-58.0 to 2372.0 °F -58.1 to -148.0 °F	± (0.4 % + 1 °F) ± (0.4 % + 1.8 °F)

p t 1000 Ω thermometer

Unit	Range	Resolution	Accuracy
°C	-10 to 70 °C	0.1 °C	± 1.2 °C
°F	14 to 158 °F	0.1 °F	± 2.2 °F

* Spec. tested under the environment RF Field Strength less than 3 V/M & frequency less than the 30 MHz only.

Appearance and specifications listed in this brochure are subject to change without notice.

