

Apollo 600

A new era in risk-based portable appliance testing and health & safety management.

Apollo 600 revolutionises safety management.

With built-in risk assessment tools for any workplace hazard and a variety of testing and inspection reports including portable appliance testing, fire detection and emergency lighting; Apollo 600 offers an all-in-one solution to managing a risk-based approach to health and safety in any workplace, reducing the burden and ensuring compliance.

Keep comprehensive client records including test and inspection reports, risk assessments and visual evidence with the help of Seaward's PATGuard 3 Health and Safety Edition software.



Key Features

- High definition colour display
- On board colour camera with flash
- Store 2000 images
- Store 50,000 appliance records
- Remote data transfer from field to office
- Bluetooth and USB connectivity
- Built in universal and electrical risk assessment tools
- Additional health & safety certificates with ability to update with more

Electrical Test Functions

- Low current earth continuity test guaranteeing accurate measurement
- Insulation resistance
- IEC lead test
- Protective conductor current
- Touch current
- Load power/current
- Alternative leakage current
- Point to point testing for fixed appliances
- RCD test
- Power socket test

Apollo 600 Users

- Dutyholders
- Health and Safety Managers
- Health & Safety Contractors
- Professional PAT Testers
- Electrical Contractors
- Facilities Managers
- Risk Assessment Professionals
- Operations Managers





► Risk-based PAT testing

Apollo 600 follows in the footsteps of Seaward's long line of trusted PAT testers, offering a comprehensive suite of fast and accurate electrical safety tests to enable any workplace appliance to be tested, including 3 phase equipment and residual current devices (RCDs). Apollo 600 also enables point to point testing of fixed appliances as required by the 4th edition of the IET Code of Practice for In-Service Inspection and Testing of Electrical Equipment.

In addition to its electrical test features, Apollo 600 has a built in electrical risk assessment tool which can be used to easily determine a risk-based suggested retest period as required by the IET 4th Edition Code of Practice for In-service Inspection and Testing.

► Visual evidence for full traceability

Apollo 600 has a built-in digital camera enabling images taken during visual inspections and risk assessments to be tagged against records in PATGuard 3 software as evidence - making for the most comprehensive and traceable record-keeping system on the market today.



► Total health and safety management

Apollo 600 features a built-in universal risk assessment tool allowing hazards to be recorded, risk scores to be calculated and corrective actions to be planned and documented easily.

For those who have responsibility for health and safety inspections outside of portable appliance testing, Apollo 600 also hosts a range of onboard reports for fire detection and emergency lighting, and it's upgradeable to include more - making it an all-in-one solution for the future of health and safety management.



► Superb software for total traceability

Apollo 600 has a large internal memory capable of storing 50,000 records and an additional 2,000 images. Its compatibility with Seaward's PATGuard 3 Health and Safety Edition software means that complete test records including images can be easily managed on a PC.

Easily transfer data to a PC remotely using Apollo 600's Bluetooth function and a compatible mobile phone or tablet; or download results onto a USB flash drive. Alternatively, transfer data directly to PC via Bluetooth or USB when back at the office. Once downloaded to PATGuard 3, it is easy to keep track of the history of test and inspection and produce reports, certificates and invoices – offering total peace of mind and quicker, easier management of scheduling inspections and tests.

► Greater efficiency through useful accessories

As with many Seaward PAT testers, Apollo 600 is compatible with a range of printers and barcode scanners, further speeding up the process of asset recognition and labelling.

Save time by uploading previously tested asset details into Apollo 600 using PATGuard 3 software - then simply scan the barcodes of assets as you go, Apollo 600 will automatically select the required test sequence appropriate to the scanned asset.



► Available Kits

Apollo 600 comes with an accessory kit as standard, which includes everything you need to get started.

A professional package is also available, offering all you need for super-efficient and comprehensive health & safety management.

	Standard Package	Professional Package
Part Number:	380A910	380A950
■ Apollo 600	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ 2x test leads with test probes and clips	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ 30 day free trial of PATGuard 3 Health and Safety Edition	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ IEC lead	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ 110V adaptor	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ Apollo 600 PAT checkbook	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ USB download lead	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ Mains power lead	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ Quick Start Guide	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ Support CD-Rom including full user manual	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ Apollo 600 carry case	<input checked="" type="checkbox"/>	<input checked="" type="checkbox"/>
■ Bluetooth printer		<input checked="" type="checkbox"/>
■ Bluetooth barcode scanner		<input checked="" type="checkbox"/>
■ Carry case for Bluetooth accessories		<input checked="" type="checkbox"/>

Technical Specifications

Earth Continuity

Test Current: +/- 200mA DC
 Display Range: 0.01 – 19.99Ω
 Pass Value: User Defined

Insulation Resistance

Test Voltage: 500V / 250V DC @ 1mA nominal
 Display Range: 0.01MΩ – 19.99MΩ
 Pass Value: User Defined

IEC Lead Test

Test voltage: 5V ac nominal
 Test: Live / Neutral Checks for o/c, s/c and crossed

Protective Conductor Current/Load

Test Voltage: Supply voltage, maximum load current 16A
 Display Ranges: 0.01mA to 19.99mA
 Pass Value: User Defined

Touch Current

Test Voltage: Supply Voltage, maximum load current 16A
 Display Range: 0.00 – 3.50mA
 Pass Value: User defined

Load Power/Current

Test Voltage: 230V +10%, -15%, maximum load current 16A
 Test Duration: Programmable up to a maximum of 255s depending on load. i.e. max duration is reduced for high loads.
 Display Range: 0.00kVA – 4.00kVA
 0.00A – 16.00A

Alternative Leakage Current

Test Voltages: >25Vac <50Vac
 Display Range: 0.00mA to 19.99mA
 Pass Value: User Defined

RCD Test

Test Voltage: 230V +10%, -15%
 Test Current: 15mA / 30mA rms sinusoidal
 Display Range: 0ms - 2000ms
 Test method: Internal isolation to avoid tripping distribution board RCD

Power Socket Test

Voltage Range: 207V – 253Vac
 Indicates configuration of voltage potential:-
 Line potential phase to earth
 Line potential phase to neutral
 Line potential neutral to earth

General

Memory size: 50,000 records & 2000 photos
 Weight: 1.5kg
 Dimensions: 230mm x 150mm x 100mm
 Power Source: Mains or rechargeable battery pack

Standard Accessories (supplied with Apollo 600)

Apollo checkbox
 2x test leads and probes with crocodile clips
 0.5m IEC lead
 110V test adaptor
 Mains power lead
 USB download cable
 30 day free trial of PATGuard 3 Health and Safety Edition
 Quick start guide
 Carry case

Optional Accessories

Test n Tag Elite bluetooth printer
 Bluetooth barcode scanner
 TPA Series 3-Phase leakage adaptor
 PATGuard 3 software

Training

R.A.1.1 - Risk Assessment for Portable Appliance Testing
 R.A.1.2 - Electrical Principles and the IET 4th Edition Code of Practice
 PAT 1.1 - Portable Appliance Testing

Services

2 year warranty subject to product registration with Seaward
 Service & Calibration by Calibrationhouse



Seaward

15-18 Bracken Hill, South West Industrial Estate,
 Peterlee, Co. Durham UK SR8 2SW

Tel: +44 (0) 191 587 8744

Email: sales@seaward.co.uk

www.seaward.co.uk