

TYPE K

TEMPERATURE PROBE

Model : TP-01, TP-02A, TP-03, TP-04

ISO-9001, CE, IEC1010



TP-01



TP-02A



TP-03



TP-04



LUTRON ELECTRONIC



The Art of Measurement

TYPE K TEMPERATURE PROBE

Model : TP-01, TP-02A, TP-03, TP-04

<i>Type K PROBE Model</i>	<i>Measurement Range</i>	<i>Accuracy</i>
(Type K) TP-01	<ul style="list-style-type: none"> * Max. short-term operating Temperature: 300 °C (572 °F). * It is an ultra fast response naked-bead thermocouple suitable for many general purpose application. 	± 0.4 %
Thermocouple Probe (Type K), TP-02A	<ul style="list-style-type: none"> * Measure Range: -50 °C to 900 °C , -50 °F to 1650 °F. * Dimension: 10cm tube, 3.2mm Dia. 	± 0.75 %
Thermocouple Probe (Type K), TP-03	<ul style="list-style-type: none"> * Measure Range: -50 °C to 1200 °C , -50 °F to 2200 °F. * Dimension: 10cm tube, 8mm Dia. 	± 0.4 %
Surface Probe (Type K), TP-04	<ul style="list-style-type: none"> * Measure Range: -50 °C to 400 °C , -50 °F to 752 °F. * Size : Temp. sensing head - 15 mm Dia. Probe length - 120 mm. 	± (0.75 % +0.5 °C)

* Appearance and specifications listed in this brochure are subject to change without notice.

0807-TP-01, TP-02A, TP-03, TP-04