


USB 3.2 Transmitter Solutions

USBSSP-TX, USB-TX Datasheet



- Quickly validate test status with comprehensive reporting that details test margins, pass/fail results, and plots in PDF, MHT and CSV formats.
- Manual Lane Switching – Support for reversible Type-C connector.

Applications

USB transmitter testing

- Host and Device silicon validation
- System, peripheral, and hub validation and integration
- Manufacturing test

Complete automation for USB testing

The automated solution for USB 3.2 simplifies transmitter testing. No longer is it a requirement that the end user be an expert in USB. The process of defining test parameters, power on/off DUT, capturing the LFPS signal, toggling the compliance patterns, making sure the compliance pattern captured is correct, showing results after each measurement is executed, and saving the test results, is fully automated in the Tektronix USB 3.2 automated test solution.

The Tektronix USBSSP-TX and USB-TX Automated Transmitter solutions provide an easy way to validate and characterize emerging USB 3.2 Type-C host controllers, hubs and devices with Tektronix MSO/DPO/70000DX/SX series oscilloscopes.

Key Offerings

- Transmitter testing
 - Provides a comprehensive automated and manual toolset for USB 3.2 Gen1 (5 Gbps) and Gen2 (10 Gbps) verification, characterization, debug, and compliance test.
 - Supports Type-C, Standard and Micro connectors for USB 3.2 Specification.
 - Provides automatic processing of USB-IF SIGTEST results without manual intervention.
 - Auto selection of sources (channels) based on the probe type selected.
 - Includes support for captive devices and their associated channels as per CTS.
 - Uses pre-recorded mode to run measurements for offline analysis and collaboration with the globally dispersed teams.
 - DPOJET plugin for USB 3.2 Type-C, Standard and Micro connectors which supports USB 3.2 specification and CTS (Gen1 & Gen2) with setup files and MOI.
 - Automatic DUT control and pattern validation to capture all required data patterns (CP0, CP1, CP9, CP10, etc.).
 - Support embedding all Channels and their respective filter files for Type-C, Standard and Micro Connectors using SDLA .

Tektronix® TekExpress USB 3.2 Report Test Report

Execution and Setup Information		DUT ID	DUT Type	Device
Date/Time	2021-05-04 03:20:07	DUT001	Scope Model	DPO7304D
Test Point	Compliance (TP4) – Far End		Scope Serial Number	Q200008
Fixture Type	USB-IF		Scope F/W Version	10.9 Build 16
Connector Type	Type C		SFC Factory S/W Calibration	PASS/PASS
Channel Type	Both Long & Short		TekExpress Version	USB 10.4.0.10 Framework 5.4.0.57
Toggle Tool	Do not use		DPOJET Version	"10.0.7.9"
Acquisition Mode	Live		CTS Version	v1.0
Total Acquisition Time	5 Minutes 20 Seconds			
Total Analysis Time	23 Seconds			
Over All Test Results	Pass			

DUT COMMENT: General Comment – USB3.2 DUT

Measurement Details	Lane	Channel	Generation	Method	Measured Value	Test Result	Margin	Low Limit	High Limit
V _{TX-DIFF-PP} -Differential PP Tx voltage swing	Lane0	Short	Gen1	DPOJET	253.007 mV	Pass	153.007 mV & 946.993 mV	100.0 mV	1.2 V
V _{TX-DIFF-PP} -Differential PP Tx voltage swing	Lane0	Long	Gen1	DPOJET	115.585 mV	Pass	15.585 mV & 1.084 V	100.0 mV	1.2 V

COMMENTS: USB 3.2 Specification, Rev 1.0, Table 6-17

Measurement Details	Lane	Channel	Generation	Method	Measured Value	Test Result	Margin	Low Limit	High Limit
TCDR_Slew_Max-Maximum Slow Rate	Lane0	Short	Gen1	DPOJET	5.109 ms/s	Pass	4.891 ms/s	N.A	10.0 ms/s
TCDR_Slew_Max-Maximum Slow Rate	Lane0	Long	Gen1	DPOJET	5.101 ms/s	Pass	4.899 ms/s	N.A	10.0 ms/s

COMMENTS: USB 3.2 Specification, Rev 1.0, Table 6-17

Measurement Details	Lane	Channel	Generation	Method	Measured Value	Test Result	Margin	Low Limit	High Limit
R _{TX-random jitter-Dual Dirac}	Lane0	Short	Gen1	DPOJET	15.386 ps	Informative	15.386 ps & 12.116 ps	0 s	3.27 ps
R _{TX-random jitter-Dual Dirac}	Lane0	Long	Gen1	DPOJET	11.424 ps	Informative	11.424 ps & 8.154 ps	0 s	3.27 ps

COMMENTS: USB 3.2 Specification, Rev 1.0, Table 6-19

TekExpress sample report in MHT format

Required test procedures (MOI) can be found at: www.tek.com/usb.



TekExpress automated framework configuration panel

Ordering Information

Key differences between USB-TX and USBSSP-TX

Feature	USB-TX	USBSSP-TX ¹
Automatic measurement selections based on device type, test type, test points, and selected probes	X	X
Automatic selection of receiver CTLE filter	CTLE only	CTLE/DFE
Automatic selection of Tx channel modeling for software channel emulation	X	X
Complete coverage of USB 3.2 Normative and Informative tests (see next table)	Gen1 (5 Gb/s)	Gen1 (5 Gb/s) and Gen2 (10 Gb/s)
Automatically save test reports and waveforms	X	X
Re-analyze prerecorded waveforms	X	X
Single test report for all measurements	Gen1 (5 Gb/s)	Gen1 (5 Gb/s) and Gen2 (10 Gb/s)
Automated LFPS measurements (setup files only)	X	X
Automated DUT toggle	X	X
Automated SIGTEST measurements	X	X

Automated TekExpress USB 3.2 (5 Gb/s and 10 Gb/s) transmitter measurements

DPO/MSO70000² Tektronix DPO (Digital Phosphor Oscilloscope) or MSO (Mixed Signal Oscilloscope) Oscilloscopes – 16 GHz and above with DPOJET and SDLA64 installed

DPO/MSO70000 Opt. USBSSP-TX³ USB 3.2 5 and 10 Gb/s Transmitter Normative and Informative Tests for TekExpress Automated Compliance Test Software

¹ USB-TX option is not a prerequisite

² Requires scope BW ≥16GHz for USB 3.2 Gen2 (10Gbps) and ≥12.5 GHz for USB 3.2 Gen1 (5Gbps).

USBSSP-UP Upgrade USB-TX (Supports 5G only) software to USBSSP-TX software package (Supports 5G & 10G)

DPOFL-USBSSP-TX³ Floating license upgrade for USB 3.2 5 Gb/s and 10 Gb/s Transmitter Normative and Informative Tests for TekExpress Automated Compliance Test Software

DPO-UP USBSSP-TX Upgrade for USB 3.2 5 Gb/s and 10 Gb/s Transmitter Normative and Informative Tests for TekExpress Automated Compliance Test Software

DPOFL-USBSSP-UP Upgrade from Floating USB TX to Floating USB SSP TX

Recommended test fixtures, cables, and tools

Item	Vendor	Quantity
USB3ET Type A and Micro B Gen1 test fixtures	USB-IF	1
USB31AET Type A & Micro B Gen2 test fixture kit	USB-IF	1
USB31CET Type C Gen1 and Gen2 test fixture	USB-IF	1
PMCABLE1M Phase Matched SMA cable set	Tektronix	2
AFG3k or AFG31k 50MHz or higher, AWG5000C, AWG5200, AWG7000C or AWG70000 (DUT State Control)	Tektronix	1
015-0572-00 BNC to SMA adapter	Tektronix	2
PWS4000 Tektronix Power Supply (optional for automatic power cycling)	Tektronix	1

Automated TekExpress USB 3.2 (5 Gb/s) transmitter measurements

DPO/MSO70000² Tektronix DPO (Digital Phosphor Oscilloscope) or MSO (Mixed Signal Oscilloscope) Oscilloscopes – 12.5 GHz and above with DPOJET and SDLA64 installed

DPO/MSO70000 Opt. USB-TX⁴ USB 3.2 5 Gb/s Transmitter Normative and Informative Tests for TekExpress Automated Compliance Test Software

DPOFL-USB-TX⁴ Floating license upgrade for USB 3.2 5 Gb/s Transmitter Normative and Informative Tests for TekExpress Automated Compliance Test Software

DPO-UP USB-TX⁴ Upgrade for USB 3.2 5 Gb/s Transmitter Normative and Informative Tests for TekExpress Automated Compliance Test Software

USB-TX-UP Upgrade USB TX solution from dongle based license to software node locked license.

³ Requires DPOJET Jitter and Eye Analysis Tools (Opt. DJA) and ≥16 GHz oscilloscope and SDLA Visualizer (SDLA64).

⁴ Requires oscilloscope with bandwidth ≥12.5 GHz and DPOJET Jitter and Eye Analysis Tools (Opt. DJA).

Recommended test fixtures, cables, and tools

Item	Vendor	Quantity
USB3ET Type A & Micro B Gen1 test fixture kit	USB-IF	1
USB31CET Type C test fixture kit	USB-IF	1
PMCABLE1M Phase Matched SMA cable set	Tektronix	2
AFG3k or AFG31k 50MHz or higher, AWG5000C, AWG7000C or AWG70000 (DUT State Control)	Tektronix	1
015-0572-00 BNC to SMA adapter	Tektronix	2

Prerequisite host system software requirements

For USBSSP-TX and USB-TX DPO/MSO70000 Series oscilloscope with Microsoft Windows 10

Required equipment for USB 3.2 testing

For complete list of required equipment's, go to <http://www.tek.com/usb>.



Tektronix is ISO 14001:2015 and ISO 9001:2015 certified by DEKRA.

ASEAN / Australasia (65) 6356 3900
 Belgium 00800 2255 4835*
 Central East Europe and the Baltics +41 52 675 3777
 Finland +41 52 675 3777
 Hong Kong 400 820 5835
 Japan 81 (120) 441 046
 Middle East, Asia, and North Africa +41 52 675 3777
 People's Republic of China 400 820 5835
 Republic of Korea +822 6917 5084, 822 6917 5080
 Spain 00800 2255 4835*
 Taiwan 886 (2) 2656 6688

Austria 00800 2255 4835*
 Brazil +55 (11) 3759 7627
 Central Europe & Greece +41 52 675 3777
 France 00800 2255 4835*
 India 000 800 650 1835
 Luxembourg +41 52 675 3777
 The Netherlands 00800 2255 4835*
 Poland +41 52 675 3777
 Russia & CIS +7 (495) 6647564
 Sweden 00800 2255 4835*
 United Kingdom & Ireland 00800 2255 4835*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777
 Canada 1 800 833 9200
 Denmark +45 80 88 1401
 Germany 00800 2255 4835*
 Italy 00800 2255 4835*
 Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90
 Norway 800 16098
 Portugal 80 08 12370
 South Africa +41 52 675 3777
 Switzerland 00800 2255 4835*
 USA 1 800 833 9200

* European toll-free number. If not accessible, call: +41 52 675 3777

For Further Information. Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit www.tek.com.

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.

13 Dec 2022 55W-23929-23
www.tek.com

Tektronix[®]