

CLAMP METER

❖ 2601C/2601CT Digital ACA Clamp Meter



(TRUE RMS / 2601CT)

- ❖ 4000 counts digital display
- ❖ Auto ranging
- ❖ Overload protections
- ❖ Safety input jacks
- ❖ Safety test leads
- ❖ Safety: EN61010-1, EN 61010-2-032, CAT IV 600V, CAT III 1000V, CE approved
- ❖ Jaw opening capability: 51mm conductor.
- ❖ Dimensions: 279mm(H)×103mm(W)×53mm(D)
- ❖ Weight: Approx. 510g

SPECIFICATIONS

- ❖ AC Current: 40A, 400A, 1000A $\pm 2.0\%$ (50-400Hz) (TRUE RMS / 2601CT)
- ❖ DC Volts: 400mV, 4V, 40V, 400V, 1000V $\pm 0.5\%$
- ❖ AC Volts: 400mV, 4V, 40V, 400V, 750V $\pm 1.5\%$ (50-500Hz) (TRUE RMS / 2601CT)
- ❖ Resistance: 400 Ω , 4k Ω , 40k Ω , 400k Ω , 4M Ω , 40M Ω $\pm 1.0\%$
- ❖ Capacitance: 4 μ F, 40 μ F, 400 μ F, 4mF $\pm 3.0\%$
- ❖ Frequency: 10Hz - 1MHz $\pm 0.1\%$
- ❖ Diode Test ❖ Continuity Test ❖ DATA Hold
- ❖ Resolution: 0.01A, 0.1mV, 0.1 Ω , 1nF, 1Hz

CHUNG INSTRUMENT ELECTRONICS INDUSTRIAL CO., LTD.