

# 30 A AC/DC Current Probe

## TCP0030A Datasheet



TCP0030A is a high-performance, easy-to-use AC/DC current probe designed for use and direct connection to oscilloscopes with the TekVPI™ probe interface. This AC/DC current measurement probe provides greater than 120 MHz of bandwidth with selectable 5 A and 30 A measurement ranges. It also provides exceptional low-current measurement capability and accuracy to current levels as low as 1 mA, important for meeting today's challenging current measurement needs.

### Key features

- Easy-to-use and accurate AC/DC current measurements
- Intelligent communication with TekVPI™ oscilloscopes provides:
  - Units scaling and readout. Automatic, on-screen readout of amps and magnitude. Manual setup is not required. Hand calculation from volts to amps is unnecessary
  - Push button degauss and Autozero functionality
  - Probe status and diagnostic indicator LEDs
  - Remote GPIB/USB probe control

- Split-core construction allows easy circuit connection
- High accuracy with typically less than 1% DC gain error
- Low noise and DC drift
- 3rd party safety certification

### Key performance specifications

- DC to >120 MHz bandwidth
- 30 A RMS maximum current capability
- 50 A peak pulse current capability
- High accuracy with typically less than 1% DC gain error
- Accurately measures current levels as low as 1 mA

### Applications

- Power supplies
- Semiconductor devices
- Power inverters/converters
- Electronic ballasts
- Industrial/consumer electronics
- Mobile communications
- Motor drives
- Transportation systems

# Specifications

All specifications apply to all models unless noted otherwise.

## Electrical characteristics

<b>Bandwidth</b>	DC to $\geq 120$ MHz
<b>Rise time</b>	$\leq 2.92$ ns
<b>Maximum DC current</b>	30 A
<b>Maximum RMS current</b>	30 A
<b>Maximum peak pulse current</b>	50 A
<b>Maximum bare wire voltage</b>	150 V CAT II, (insulated wire 300 V CAT II)
<b>Sensitivity</b>	1 mA (on oscilloscopes that support 1 mV/div setting)
<b>DC accuracy</b>	$\pm 1\%$ typical $\pm 3\%$ warranted
<b>Maximum Amp-Second product</b>	500 A $\cdot\mu$ s (in 30 A range)
<b>Insertion impedance</b>	1 m $\Omega$ at 10 kHz 3.5 m $\Omega$ at 100 kHz 0.08 $\Omega$ at 1 MHz 0.15 m $\Omega$ at 10 MHz 0.7 $\Omega$ at 100 MHz 0.85 $\Omega$ at 120 MHz
<b>Signal delay</b>	14.5 ns
<b>Current ranges</b>	5 A and 30 A
<b>Power requirements</b>	TCP0030A is powered directly by oscilloscopes with the TekVPI™ interface. Note: For best support, download and install the latest version of the oscilloscope software from <a href="http://www.tek.com">www.tek.com</a> .

## Physical characteristics

<b>Probe head</b>	
<b>Length</b>	20 cm (7.77 in)
<b>Width</b>	1.6 cm (0.625 in)
<b>Height</b>	3.2 cm (1.25 in)
<b>Maximum conductor size</b>	5 mm (0.197 in)
<b>Cable Length</b>	200 cm (79 in)
<b>Shipping Weight</b>	1.55 kg (3.44 lb)

**EMC environment and safety****Temperature**

<b>Operating</b>	0 °C to 50 °C (32 °F to 122 °F)
<b>Nonoperating</b>	-40 °C to +75 °C (-40 °F to 167 °F)

**Humidity**

<b>Operating</b>	5% to 95% Relative Humidity (RH) at up to +30 °C; 5% to 85% RH above 30 °C up to +50 °C, noncondensing
<b>Nonoperating</b>	5% to 95% Relative Humidity (RH) at up to +30 °C; 5% to 85% RH above 30 °C up to +75 °C, noncondensing

**Altitude**

<b>Operating</b>	Up to 3,000 m (10,000 ft.)
<b>Nonoperating</b>	Up to 12,192 m (40,000 ft.)

<b>Compliance labeling</b>	CE (European Union), WEEE (European Union)
----------------------------	--

**Ordering information****Models**

TCP0030A	AC/DC Current Probe
----------	---------------------

**Standard accessories**

Instruction manual	071-3006-xx
Probe ground lead - 6 in. length	196-3120-xx
Nylon carrying case	016-1952-xx

**Recommended accessories**

Current Loop, 1 Turn, 50 $\Omega$ with BNC connector used for Performance Verification	Order 067-2396-00
--	-------------------

**Warranty**

One year parts and labor.

## Service options

Opt. C3	Calibration Service 3 Years
Opt. C5	Calibration Service 5 Years
Opt. D3	Calibration Data Report 3 Years (with Opt. C3)
Opt. D5	Calibration Data Report 5 Years (with Opt. C5)
Opt. R3	Repair Service 3 Years (including warranty)
Opt. R3DW	Repair Service Coverage 3 Years (includes product warranty period). 3-year period starts at time of instrument purchase
Opt. R5	Repair Service 5 Years (including warranty)
Opt. R5DW	Repair Service Coverage 5 Years (includes product warranty period). 5-year period starts at time of instrument purchase
Opt. SILV600	Standard warranty extended to 5 years



Tektronix is registered to ISO 9001 and ISO 14001 by SRI Quality System Registrar.

ASEAN / Australasia (65) 6356 3900  
Belgium 00800 2255 4835\*  
Central East Europe and the Baltics +41 52 675 3777  
Finland +41 52 675 3777  
Hong Kong 400 820 5835  
Japan 81 (3) 6714 3010  
Middle East, Asia, and North Africa +41 52 675 3777  
People's Republic of China 400 820 5835  
Republic of Korea 001 800 8255 2835  
Spain 00800 2255 4835\*  
Taiwan 886 (2) 2722 9622

Austria 00800 2255 4835\*  
Brazil +55 (11) 3759 7627  
Central Europe & Greece +41 52 675 3777  
France 00800 2255 4835\*  
India 000 800 650 1835  
Luxembourg +41 52 675 3777  
The Netherlands 00800 2255 4835\*  
Poland +41 52 675 3777  
Russia & CIS +7 (495) 6647564  
Sweden 00800 2255 4835\*  
United Kingdom & Ireland 00800 2255 4835\*

Balkans, Israel, South Africa and other ISE Countries +41 52 675 3777  
Canada 1 800 833 9200  
Denmark +45 80 88 1401  
Germany 00800 2255 4835\*  
Italy 00800 2255 4835\*  
Mexico, Central/South America & Caribbean 52 (55) 56 04 50 90  
Norway 800 16098  
Portugal 80 08 12370  
South Africa +41 52 675 3777  
Switzerland 00800 2255 4835\*  
USA 1 800 833 9200

\* European toll-free number. If not accessible, call: +41 52 675 3777

Updated 10 April 2013

**For Further Information.** Tektronix maintains a comprehensive, constantly expanding collection of application notes, technical briefs and other resources to help engineers working on the cutting edge of technology. Please visit [www.tektronix.com](http://www.tektronix.com).

Copyright © Tektronix, Inc. All rights reserved. Tektronix products are covered by U.S. and foreign patents, issued and pending. Information in this publication supersedes that in all previously published material. Specification and price change privileges reserved. TEKTRONIX and TEK are registered trademarks of Tektronix, Inc. All other trade names referenced are the service marks, trademarks, or registered trademarks of their respective companies.



12 Apr 2013

51W-19042-7

[www.tektronix.com](http://www.tektronix.com)

**Tektronix**

